(19) World Intellectual Property Organization

International Bureau



. | 1886 | 1886 | 1886 | 1886 | 1886 | 1886 | 1886 | 1886 | 1886 | 1886 | 1886 | 1886 | 1886 | 1886 | 1886 | 1

(43) International Publication Date 3 March 2005 (03.03.2005)

PCT

(10) International Publication Number WO 2005/019365 A2

(51) International Patent Classification7: C09J 4/00, 5/02

(21) International Application Number:

PCT/IB2004/051397

(22) International Filing Date: 5 August 2004 (05.08.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 03102607.3

20 August 2003 (20.08.2003) EP

- (71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): VERSTEGEN, Emile, J., K. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). KLOOSTERBOER, Johan, G. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). STAPERT, Hendrik, R. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). NELJZEN, Jacobus, H., M. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). VAN SANTEN, Helmar [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (74) Agent: UITTENBOGAARD, Frank; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,

MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Published:

 without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: NON-LEACHING ADHESIVE SYSTEM AND ITS USE IN A LIQUID IMMERSION OBJECTIVE

(57) Abstract: A non-leaching adhesive system and its use in a liquid immersion objective for immersion-writing of masters for optical discs are disclosed. The adhesive system comprises at least one monomer, selected from among the group of acrylate and methacrylate monomers, allylic monomers, norbornene monomers, hybrid monomers thereof, containing chemically different polymerizable groups, and multifunctional thiol monomers, provided that said thiol is used in combination with at least one of said non-thiol monomers; and a polymerization initiator. At least one of said monomers, not being a thiol, is provided with at least two functional polymerizable groups to obtain a crosslinked polymer network. The polymerization initiator is preferably an initiator that can be activated both thermally and with UV radiation. The adhesive system may further contain a reactive diluent. Further the use of the present adhesive system in mounting a liquid immersion objective is disclosed.

